



SEMI-AUTOMATIC CIRCULAR SAWING MACHINES

NTS 315 MACC CIRCULAR SAW



Features

- The saw head guides over a vertical column, making it stable and vibration-free.
- High cutting speed and low saw blade wear
- Saw head adjustable 45° right and 60° left
- Lockable miter positions (45°-0°-45°-60°)
- Continuous regulation of the saw feed !!!
- Saw blade with 2 speeds 33x66 rpm
- Course of the vertical movement of the saw head adjustable with limit switches
- Easily adjustable material clamp
- Schip breaker to keep saw blade free from chips
- Machine base and built-in electro cooling pump
- Emergency stop
- Accessory set with keys
- Dutch manual
- CE certificate

Operation

- Starting by pressing the start button
- The clamp closes after which the saw blade starts
- Saw head moves down
- Return of saw head to starting position
- Clamp opens

Options

- 3 phase motor 17/34 rpm for stainless steel
- additional clamp



MAC NTS315400 - W38211

Weight	300 kg
Power max.	1800 W
Speed min.	33 rpm
Speed max.	66 rpm
Diameter saw blade	315 mm
Clamp opening	160 mm
Cutting capacity square 0°	90 mm
Cutting capacity square 45°	90 mm
Cutting capacity square 60°	70 mm
Capacité de coupe rond plein 0°	70 mm
Cutting capacity round full 45°	70 mm
Cutting capacity round full 60°	70 mm
Cutting capacity tube 0°	100 mm
Cutting capacity tube 45°	100 mm
Cutting capacity tube 60°	80 mm
Voltage	3x400 V
Cutting capacity rectangle flat 0°	135x80 mm
Cutting capacity rectangle flat 45°	100x80 mm
Cutting capacity rectangle flat 60°	70x70 mm
Length	650 mm
Width	1500 mm
Height	2000 mm